



Triggered Spark Gap – TSG11302S



- Triggering air gap technology provides low let-through voltage, which offers superior protection compared to traditional spark gaps
- Effective equipotential bonding provides N-PE equalization protection bond on TT power distribution systems
- Can be used L-PE or L-N due to follow current control



Part Number	TSG11302S
Nominal System Voltage (Un)	240 VAC
Max Continuous Operating Voltage (Uc)	440 VAC
Voltage Protection Level (Up)	1,500 V @ 3 kA 2,300 V @ 20 kA
Max Discharge Current (Imax)	130 kA 8/20 μ s 50 kA 10/350 μ s
Follow Current Extinguishing Capability @ Un	43 kA
Impulse Current (Iimp)	50 kA 10/350 μ s
Max Operating Current	2.2 mA
Protection Modes	Single
Technology	Triggered Spark Gap
Frequency	50 – 60 Hz
Enclosure Material	UL [†] 94V-0 Thermoplastic
Enclosure Rating	IP 20 NEMA [®] -1
Mounting	35 mm top hat DIN rail
Status Indication	LED for line connected modes
Temperature	-40 to 80 °C
Module Width	2 M
Depth (D)	68 mm
Height (H)	90 mm
Width (W)	36 mm
Unit Weight	0.3 kg
Complies With	IEC [®] 61643-1 Class I, Class II ANSI [®] /IEEE [®] C62.41.2-2002 Cat A, Cat B, Cat C

Part Number	TSG11302S
	ANSI®/IEEE® C62.41.2-2002 Scenario II, Exposure 3, 100 kA 8/20 µs, 10 kA 10/350 µs
Certifications	C-Tick
Standard Packaging Quantity	1 pc
UPC	78285647543
EAN-13	8711893132670

ANSI is a registered trademark of American National Standards Institute. IEC is a registered trademark of the International Electrotechnical Commission. IEEE is a registered trademark of The Institute of Electrical and Electronics Engineers, Inc. NEMA is a registered service mark of National Electrical Manufacturers Association. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

Pentair products shall be installed and used only as indicated in Pentair's product instruction sheets and training materials. Instruction sheets are available at erico.pentair.com and from your Pentair customer service representative. Improper installation, misuse, misapplication or other failure to completely follow Pentair's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2017 Pentair All rights reserved

Pentair, CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH and LENTON are owned by Pentair or its global affiliates.

All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.